

Sanitary cubicles and partitions for dry areas SLKA 01W18N



Illustrative photo

Characteristics

- designed for dry areas
- for separating individual WC cubicles
- custom production
- walls made of 18 mm thick chipboard panels
- AISI 304 stainless steel fittings
- anodized aluminum profiles
- hygienically safe surface

Technical Specification

Dimensions	total height 2100 mm, cubicle width according to customer specification, gap height from floor 150 mm
Wall filling	chipboard 18 mm thick, standard color grey or white, other colors at extra charge
Doors	chipboard 18 mm thick, color standard grey or white, other colors available for an extra charge self-closing hinges, stainless steel door closer with free/occupied indicator or handle with lock
Fittings	stainless steel AISI 304
Construction	top profile and U profile for panel mounting to wall, anodized aluminum

Supply Specification

SLKA 01W18N (order number) - Supply No. 40014 set of parts for assembly according to order

Components



U profile for attaching panels to the wall (anodized aluminium)



upper tubular profile, diameter 30 mm (stainless steel); for panel widths up to 60 cm, the upper profile does not need to be used




adjustable foot (stainless steel)



door handle for cubicle (stainless steel)



handle with lock (stainless steel)



door closer with free/occupied indicator or handle



self-closing hinges (stainless steel)



hook (stainless steel)



door stop (stainless steel)